



HOSHIZAKI

NUGGET ICE MAKER, MODULAR FM-480AWKE-R452N-SB

Serie prodotto: FM

Codice prodotto: F082-C223



This Hoshizaki FM-480AWKE-R452N-SB is a modular nugget ice maker producing up to 380 kg of high-quality nugget ice per 24 hours.

Hoshizaki FM ice makers generate quality granular ice, such as nugget ice. In cocktails, the dry and hard ice nuggets are the ideal cooling agent, as they deliver just the right amount of dilution, especially for strong spirited drinks, for example, Mojitos and Tiki Cocktails. The ice maker's extruding head performs a high compression to yield harder and drier ice nuggets.

The FM-480AWKE-R452N-SB uses refrigerant R452A.

Material

The exterior and the auger are made of stainless steel. The closed water circuit provides maximum protection against any type of contamination during ice production. All Hoshizaki machines are easy to use, clean, and maintain.

Unique Technology

The inner workings of our Nugget Ice Makers are designed to prevent unpleasant calcification and bacterial contamination. For example, the use of carbon graphite bushings instead of conventional ball bearings allows the machine to work entirely without grease.

Smart Design

Like all Hoshizaki Ice makers, the FM-480AWKE-R452N-SB is designed to last and comes with smart design extras, such as the intuitive control display for preventive maintenance.

Perfect Fit

Need to amp up your production capacity? The variable setups with modular bins and bases allow the user to mix and match depending on individual requirements and conditions. The dimensions of the FM-480AWKE-R452N-SB are 560 x 700 x 780 mm.

Plug&Play

The smart plug-and-play design guarantees an easy and quick set-up.

SPECIFICATIONS

Nome del prodotto	Nugget Ice Maker, Modular
Capacità produttiva (kg/24h) circa	380
Collegamento elettrico	1/220 - 240V/50Hz
Consumo Elettrico (kW)	1.45
Dimensioni L x P x A (mm)	560 x 700 x 780
Tipo di ghiaccio	Nugget
Refrigerante	R452A
Sistema di raffreddamento	Water Cooled
Configurazione del prodotto	Modular

Peso netto (kg)	95
Peso lordo imballato (kg)	102
Corrispondente contenitore/i	B140SA, B210SA, B340SA
Consumo acqua fabbricatore (m ³ /24o) approx. (10°C aria / 10°C acqua)	0.38
Consumo acqua fabbricatore (m ³ /24o) approx. (21°C aria / 15°C acqua)	0.35
Consumo acqua fabbricatore (m ³ /24o) approx. (32°C aria / 21°C acqua)	0.32
Flusso acqua (m ³ /24o) di raffreddamento del condensatore approx. (10°C aria / 10°C acqua)	1.18
Flusso acqua (m ³ /24o) di raffreddamento del condensatore approx. (21°C aria / 15°C acqua)	1.652
Flusso acqua (m ³ /24o) di raffreddamento del condensatore approx. (32°C aria / 21°C acqua)	2.44