



This Hoshizaki FM-600AWKE-R452-SB is a modular flake ice maker producing up to 570 kg of high-quality flake ice per 24 hours.

Hoshizaki FM ice makers generate quality granular ice, such as Flake ice. The light texture of granular ice has a quick cooling effect, creating an environment of uniform temperatures, without causing unpleasant freezer-burn. This is why Hoshizaki Flake ice is highly popular and considered the ideal material to prepare and layer hygienic and attractive food displays.

For flake ice, the extruding head is equipped with wide channels and multi-blade cutters.

The FM-600AWKE-R452-SB uses refrigerant R452A.

Material

The exterior and the auger are made of stainless steel. The closed water circuit provides maximum protection against any type of contamination during ice production. All Hoshizaki machines are easy to use, clean, and maintain.

Unique Technology

The inner workings of Flakers are designed to prevent unpleasant calcification and bacterial contamination. For example, the use of carbon graphite bushings instead of conventional ball bearings allows the machine to work entirely without grease.

Smart Design

Like all Hoshizaki Ice makers, the FM-600AWKE-R452-SB is designed to last and comes with smart design extras, such as the intuitive control display for preventive maintenance.

Perfect Fit

Need to amp up your production capacity? The variable setups with modular bins and bases allow the user to mix and match depending on individual requirements and conditions. The dimensions of the FM-600AWKE-R452-SB are 560 x 700 x 780 mm.

Plug&Play

The smart plug-and-play design guarantees an easy and quick set-up.

SPECIFICATIONS

Nome del prodotto	Flaker, Modular	Peso netto (kg)	107
Capacità produttiva (kg/24h) circa	570	Peso lordo imballato (kg)	114
Collegamento elettrico	1/220 - 240V/50Hz	Corrispondente contenitore/i	B140SA, B210SA, B340SA
Consumo Elettrico (kW)	1.705	Consumo acqua fabbricatore (m³/24o) approx. (10°C aria / 10°C acqua)	0.6
Dimensioni L x P x A (mm)	560 x 700 x 780	Consumo acqua fabbricatore (m³/24o) approx. (21°C aria / 15°C acqua)	0.56
Tipo di ghiaccio	Granulare	Consumo acqua fabbricatore (m³/24o) approx. (32°C aria / 21°C acqua)	0.52
Refrigerante	R452A	Flusso acqua (m³/24o) di raffreddamento del condensatore approx. (10°C aria / 10°C acqua)	1.085
Sistema di raffreddamento	Water Cooled	Flusso acqua (m³/24o) di raffreddamento del condensatore approx. (21°C aria / 15°C acqua)	1.773
Configurazione del prodotto	Modular	Flusso acqua (m³/24o) di raffreddamento del condensatore approx. (32°C aria / 21°C acqua)	2.605